

Autel AC Compact.

Productspecificaties



MaxiCharger AC Compact

The ultimate cost-effective AC Charger



Fast

High-value choice to liven up home charging

- Up to 22kW AC charging, 3 times of the speed of common AC chargers



Simple

Optimized installation and maintenance costs

- Smaller than a mini tablet, lighter than a Laptop
- Features modular design, it is easier than ever to install and maintain at lower costs



Reliable

Considerate safety design in every situation

- Reliable charging in all scenes
- AC 30mA + DC 6mA leakage protection

A Closer Look at the MaxiCharger AC Compact



Charging Cable Can Be Permanently Locked



Compatible with all EVs with a Type 2 plug



Adaptive Load Management



Power Sharing



Autel Charge App



IK10 High Impact Resistance



24/7 Global Support



Three-year Warranty

Technical Specifications

Product Information

Charging mode	Mode 3
Input/output power rating and current	Single phase up to 7.4kW/32A; Three phase up to 22kW/32A
Input/output voltage	230V±15%, single phase; 400V±15%, three phase; 50Hz (UK: 230V±10%, single phase; 400V±15%, three phase; 50Hz)
Network type	Single phase 3 Wire – L1, N, PE Three phase 5 Wire – L1, L2, L3, N, PE
Connector type	IEC 62196 type 2 normal socket IEC 62196 type 2 socket with shutter
Residual current detection	AC 30mA + DC 6mA
Protection	Overcurrent, overvoltage, undervoltage, integrated surge
Card reader (Optional)	protection ISO 14443
Power measurement accuracy	+/- 2.0%

General Characteristics

IP and IK rating	IP54, IK10, indoor or outdoor
Operating altitude	installation 2000m
Operating temperature range	-30°C ~ +50°C
Storage temperature range	-40°C ~ +70°C
Mounting	Wall or floor using a pedestal
Dimensions (H×W×D)	202 × 202 × 115 mm

User Interface

Status indication	LED / APP
User interface	Autel Charge APP; Autel Charge Cloud
Connectivity Communication protocols	Bluetooth, Wi-Fi, Ethernet, RS485, 4G, Modbus TCP/IP
User authentication	OCPP 1.6J APP, RFID card, AutoStart

Software Update

OTA updates via web portal

Certification and Standards

Safety and compliance	IEC/EN 61851-1, EN 50663, EN 50665, IEC/EN 62955
Certification	CE (TÜV)
Warranty	36 months, warranty extension possible

* All pictures shown are for illustration purpose only, actual product and specifications may vary due to product enhancement



Orange Charging B.V.

Phone: +31(0)85 105 47 50

E-mail: info@orangecharging.com

Website: orangecharging.com



Orange Charging